


This document contains the proprietary information of Tandemloc, Inc. and your access and use shall be, and is at all times, pursuant to and limited by the Tandemloc, Inc. Terms of Use. You shall not, and shall not encourage, assist, or authorize another party to copy, distribute, publicly display, modify, reverse engineer, decompile, or take any other action to reproduce this document or the information contained herein.

©2019 by Tandemloc, Inc.
Dimensions are subject to manufacturing tolerance and change.



- NOTES:
- PART NO.: AT14A025-240-PA, 144"-240" TELESCOPIC SPREADER
AT14A025-240SPA, 144"-240" TELESCOPIC SPREADER WITH TOP SLING
 - WLL: 25,000 LB. @ 45° MINIMUM
 - PROOF TESTED TO 125% (31,250 LB.) AND CERTIFIED
 - STANDARD SPECIFICATION # EAD21000A APPLIES
 - FINISH: SANDBLAST AND PRIME AND PAINT YELLOW
 - CALCULATED WEIGHT: 600 LB. SPREADER WITH SLING: 698 LB.
 - DESIGNED AND MANUFACTURED TO MEET OR EXCEED ASME B30.20 AND BTH-1, DESIGN CATEGORY B, SERVICE CLASS 0.

** DO NOT SIGN IF CHANGES ARE REQUIRED **

CUSTOMER APPROVAL: _____

DATE: _____

<small>1 1/2" DIMENSIONS APPLICABLE UNLESS OTHERWISE NOTED. DIMENSIONS ARE IN INCHES & TOLERANCES ARE: .XX ±.01, .XXX ±.005, .XXX ±.01</small>	<small>1" DIMENSIONS APPLICABLE UNLESS MAX. CLOSING TH. IS: 0 TO 4" ±.03, 4.01" TO 7" ±.04, 7.01" TO 10.5" ±.05, OVER 10.5" ±.0625</small>	TANDEMLOC				
		AT14A025-240-PA 144"-240" TELESCOPIC SPREADER				
<small>THIS DOCUMENT CONTAINS OUR BEST WORKING DESIGN. IT IS THE PROPERTY OF TANDEMLOC, INC. SUBSTITUTION OR REVISIONS WITHOUT THE WRITTEN APPROVAL OF TANDEMLOC, INC. IS EXPRESSLY PROHIBITED.</small>	<small>APPROVALS</small> <small>DATE</small>	<small>DATE</small> 04-01-19	<small>REV.</small> D	<small>QTY</small> 65059	<small>REV. NO.</small> SAT14A025-240-PA-	<small>REV.</small> 1 OF 1