

BLACK STAGE SLINGS

These lightweight roundslings are ideal for easy and inconspicuous suspension of stage sound and lighting equipment. Black sleeve material helps the sling blend into the surroundings. *Lift-All* stage slings include all of the *Tuflex*® features and benefits except that the color coding of the slings is achieved by using a color-coded identification tag. Double-wall sleeve material is standard.



| Part Number | Color of Tags | Rated Capacity (lbs.)* | | | Min. Length (ft.) | Approximate Measurements | | | |
|-------------|---------------|------------------------|--------|--------|-------------------|--------------------------|-------------------------|---------------------|--------------------------|
| | | Vertical | Choker | Basket | | Weight (lbs./ft.) | Body Dia. Relaxed (in.) | Contact Width (in.) | Min. Hardware Dia. (in.) |
| BSEN30 | Purple | 2,600 | 2,100 | 5,200 | 1-1/2 | 0.2 | 5/8 | 1-1/8 | 7/16 |
| BSEN60 | Green | 5,300 | 4,200 | 10,600 | 1-1/2 | 0.3 | 7/8 | 1-1/2 | 5/8 |
| BSEN90 | Yellow | 8,400 | 6,700 | 16,800 | 3 | 0.4 | 1-1/8 | 1-7/8 | 3/4 |



TUFLEX WIDE-LIFT

Wide Load Support and Balance

Tuflex Wide-Lift slings distribute the load over a wide area and offer better balance of larger loads, whether heavy or light.

Features and Benefits

Maintains all the basic *Tuflex* features plus...

Promotes Safety

- Wide body distributes load over wide area and offers improved stability.

Saves Money

- Bearing point of eyes can be shifted to prolong sling life.
- Custom sizes available to fit your needs.

Saves Time

- Standard eye length is 12", making hook-up easy and fast.
- Standard body width is 12", making load balancing easier.



Note:

Wide-lift slings should only be used in basket hitch.

Consult *Lift-All* for special requirements.

| Code | Color of Eyes | Vertical Basket Hitch Rated Capacity* (lbs.) |
|---------|---------------|----------------------------------------------|
| WLEN30 | Purple | 5,200 |
| WLEN60 | Green | 10,600 |
| WLEN90 | Yellow | 16,800 |
| WLEN120 | Tan | 21,200 |

* **WARNING** Do not exceed rated capacities. Sling tension increases as the angle from horizontal decreases. Slings should not be used at angles of less than 30°. Refer to the Effect of Angle chart in the General Information section of this catalog. **Always protect synthetic slings from being cut by corners and edges. See the Sling Protection section in this catalog.**