PALLET TRUCK WITH AGM BATTERIES, SCALE & RIDER PLATFORM - EPT-2748-45-SCLRPAGM *** ANY ADDITIONS. DELETIONS. OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE *** ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON APPROX WEIGHT: 1082 lbs. For use with open bottom pallets only 51-3/8 (1305mm) 31-1/2 (800mm) 3 5/8" MINIMUM CLEARANCE REQUIRED 00000000 00000000 00000000 8 ± 1/16 (205mm) 0 73-1/4 (1860mm) -48 (1220mm $3^{\frac{1}{2}} \pm \frac{1}{16}$ IND221 SCALE HEAD -2-7/16 (62mm) (89mm) -30-3/16 (766mm) - • 7-1/16 (80mm) 30-3/16 (766mm) **DIMENSION TOLERANCE ± 1/2"** 27 (685mm) I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS REPRESENTED SATISFIES DESIGN AND DIMENSION REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO CONFIRM PRODUCT AND INSTALLATION R 68-7/8 (1750mm) Ρ AND LOCAL REGULATIONS AND STANDARDS R UNITS REQUIRING APPROVAL DRAWINGS OR 0 MODIFIED ARE NON-RETURNABLE [] As drawn [] As marked Signed: Date: STANDARD FEATURES MODEL NUMBER: EPT-2748-45-SCLRPAGM **Printed Name:** CAPACITY: 4500 LBS CONTINUOUS LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING DISTRIBUTOR'S NAME: LIFT HEIGHT: 8 ± 1/16" LOWERED HEIGHT: 3 1/2" ± 1/16" W.O.# X VESTIL MANUFACTURING DRIVE WHEEL: Ø10 X 3 1/8" DRAWN BY: TM DATE: 5/31/2022 SALES: X LOAD ROLLER: Ø2 3/4 X 2.9" BATTERY: 4 x 6V / 210 Ah-AGM FILE NAME: SPECIAL FEATURES SCALE: NTS TOUGH BAKED IN POWDER COATED QUOTED LEAD TIME: X **BLACK AND YELLOW FINISH** NONE QUOTE # EPT-2748-45-**SCLRPAGM**