## APPROX WEIGHT: 5.67 lbs. EXTRUDED ALUMINUM HOSE & CABLE CROSSOVER RAMP - HCR-24-BRN DOES NOT INCLUDE WEIGHT OF POWER OR PACKAGING!!! \*\*\* ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE \*\*\* ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON - 1 1/16" 3/4" 2 5/8" 7 1/8" DIMENSION TOLERANCE ± 1/2" I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS REPRESENTED SATISFIES DESIGN AND DIMENSION REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO CONFIRM PRODUCT AND INSTALLATION COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS AND STANDARDS. **NOTE**: HOLF IS FOR POWDER COATED UNITS ONLY ANY MODIFIED UNITS ARE NON-RETURNABLE 0 [ ] As drawn [ ] As marked STANDARD FEATURES SPECIAL FEATURES Signed: Date: NONE MODEL NUMBER: HCR-24-BRN Printed Name: SINGLE WHEEL CAPACITY: 10,000 LBS LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING **OVERALL WIDTH: 7 1/8"** DISTRIBUTOR'S NAMF:

**OVERALL LENGTH: 24" OVERALL HEIGHT: 1 1/16"** USABLE WIDTH: 25/8" **USABLE HEIGHT: 3/4"** 

FINISH: BROWN

FOR INTERNAL USE ONLY PROJECT SIGN OFF **SALES** ENG. FAB. POWER

P.O.# X

W.O.# X VESTIL MANUFACTURING SALES: X DRAWN BY: K.YEAKLE 05/10/12 reference: X FILE NAME: SCALE: 1:2

QUOTED LEAD TIME: Y OUOTF # 29-007-043-002 Χ