

# GUY WIRE DISPENSER

## WARNING

Cancer and Reproductive Harm: [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



## KEY FEATURES

- ✓ Handles Guy Wire OD up to 1/2"
- ✓ Permanently Mounts to truck or other surface
- ✓ Smooth pay out operation thanks to high load sealed bearings
- ✓ Standard and Large Size versions

Slingco's guy wire dispenser saves linemen time, effort, and keeps them safe. Efficiently dispense and take up excess guy wire from a permanently mounted source. Operation of the dispenser is kept smooth thanks to the high load sealed ball bearing.

Slingco's guy wire dispenser is constructed of high strength steel coated in a durable black finish to enable the unit to endure the harsh outdoor environment.

Easy to operate release knobs allow for quick and easy loading and unloading.

| Slingco Part No. | Max Wire Size (in) | Max Wire Size (mm) | Coil Diameter Range (in) | Coil Diameter Range (mm) | Coil Width Capacity (in) | Coil Width Capacity (mm) | Height (in) | Height (mm) | Width (in) | Width (mm) | Depth (in) | Depth (mm) | Weight (lb) | Weight (kg) |
|------------------|--------------------|--------------------|--------------------------|--------------------------|--------------------------|--------------------------|-------------|-------------|------------|------------|------------|------------|-------------|-------------|
| ZWM09207         | 0.5                | 12.7               | 22 - 31                  | 559 - 787                | 4.75                     | 120                      | 34.5        | 876         | 35.625     | 829        | 9.25       | 235        | 45          | 20.5        |
| ZWM12496         | 0.5                | 12.7               | 32 - 36                  | 813 - 914                | 8.75                     | 222                      |             |             |            |            |            |            | 54          | 24.5        |

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco America, Inc.

### Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/- 10%. Please contact us if you have any questions.

**Range dimension overlaps** If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.



## GET IN TOUCH

 1 888 685 9478  
 [sales@slingcoamerica.com](mailto:sales@slingcoamerica.com)