Cage Code: 65059 | Drawing No: SAS25A15-48A-2PA | Revision: - | Sheet: 1 of 1 UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES 49.00 OVERALL LENGTH NOTES: 1. PART NO.: AS25A15-48A-2PA, 7.5 TON FORKLIFT BEAM 2. WLL: 15.000 LB. 3. PROOF TESTED TO 125% (18,750 LB.) AND CERTIFIED 4. STANDARD SPECIFICATION # EAD21000A APPLIES 5. FINISH: SANDBLAST, PRIME AND PAINT SAFETY YELLOW 6. CALCULATED WEIGHT: 106 LB. 7. DESIGNED AND MANUFACTURED TO MEET OR EXCEED F O ASME B30.20 AND BTH-1, DESIGN CATEGORY A, OB SERVICE CLASS 0. 7.25 OVERALL **RETAINING CHAIN** WIDTH 2.5" RED VINYL **ATTACHMENT POINT 2" BLACK VINYL BOTH SIDES BOTH SIDES** WLL 15,000 LB FORK TIGHTENING 20.56 BOLT **OVERALL TYP. 4 PLACES** 2.50 HEIGHT SWIVEL HOOK W/ SAFETY LATCH 35.00 48.00

7.5 TON FORKLIFT BEAM, WLL 15,000 LB. (AS25A15-48A-2PA)

To avoid lifter failure, potential death and property damage, never exceed WLL (Working Load Limit).

This document contains the proprietary information of Tandemloc, Inc. and your access and use shall be, and is at all times, pursuant to and limited by the Tandemloc, Inc. Terms of Use.

You shall not , and shall not encourage, assist, or authorize another party to copy, distribute, publicly display, modify, reverse engineer, decompile, or take any other action to reproduce this document or the information contained herein. © Copyright 2014 by Tandemloc, Inc.

Dimensions are subject to manufacturing tolerance and change.



Email: info@tandemloc.com • www.tandemloc.com 824 Highway 101 • Havelock, NC 28532 Tel: 1.800.258.7324 (252.447.7155) FAX 1.800.892.3273 (252.447.5502)

Tandemloc, Inc. designs, manufactures and tests lifting, securing and mobilizing components for all industries. See our website for details and important safety information.

Read all safety labels and instructions prior to use. Product to be used by qualified personnel only.