8	7		6	5	4		3	
	Tel (+1) 71 Info@liftingequipme	3 489 5335 entstore.us						
	<u>#</u>		· · · · ·					Gr
LIFTING EQU	IPMENT STO	DRE	1					со
								stc
6mm (1/4") Grade 10 Si					Master link			
	locking hook the oth	er						AS
	(WLL 2700lbs)			-				AS
Description								
Master link Connector		1		C				Co
	aring longth	1		. 15)				AS
Frade 10 chain to suit be Clevis self locking		1		157	Grade 10	Connocto		
					Gidde IU	connecto)i	Ch
8mm (5/16") Grade 10 S								to
	locking hook the oth	er						the
	(WLL 5700lbs)							slir
Description		QTY		11 I				
Masterlink		1				- · ·		Ch
Connector		1	0		Grade 10 Grade	Chain		he
ade 10 chain to suit be		1	E					all
Clevis self locking		1		G	rade10 Chain	taq		sp
	ingle Leg Chain Sling,	Master		Ŭ Ť				.6
Link one end , Self	locking hook the oth	er		P				The
WLL 4 t (WLL 8800 lbs)		2		(A) William Hacke	ett		lifti
Description	0		Ē					20
Masterlink		1	-		10/11			de
Connector		1	E		WLL :			00
rade 10 chain to suit be		1						00
Clevis self locking	hook	1		TT I I I I I I I I I I I I I I I I I I	Serial No:			Ba
13mm (1/2") Grade 10 S	ingle Leg Chain Sling,	Master						for
Link one end , Self	locking hook the oth	er	ב הס					
WLL 6.7 t	(WLL 15000lbs)				Chai	n tag		De
Description	0	QTY				-		ac
Masterlink		1	ם		allac	hment	loop	uc
Connector		1						
Grade 10 chain to suit be	aring length	1		1 M	Grade 10 (
Clevis self locking	hook	1			Self locker			
16mm (5/8") Grade 10 S	ingle Leg Chain Sling,	Master					FINISH:	
Link one end , Self	locking hook the oth	er						
WLL 10 t (WLL 22600lbs)							
Description		QTY		• /			NAME DRAWN Will Frater	SIGNATURE
Masterlink		1				-	CHK'D	
Connector		1				4	APPV'D	
Grade 10 chain to suit be	aring length	1	L			-	JNLESS OTHERWISE	
Clevis self locking		1				S	SPECIFIED DIMENSIONS ARE IN MILLIMETERS	MATERIAL:
						1	OLERANCES:	
							INEAR: ANGULAR:	WEIGHT:

F

Ε

D

С

В

Α

2

rade 10 Alloy Chain Slings omply with the following andards: F

Ε

D

С

SME B30-09-18 -G10 Sling STM A973/A973M - G10 Sling

omponents - BS EN 1677-1 STM A952-A952M , ASME B30.26

hain & Components- Proof tested 2.5 times WLL - This exceeds e ASTM requirements. Assembled ing proof tested to 2 times the WLL.

hain - Tensile strength following eat treatment meets or exceeds I existing ASTM and OSHA pecification requirements.

nese products are sutiable for ting operations from -40° c to 00° c. Consult our technical epartment for operations utside of this range.

atch marks on all components r traceability.

eclaration of conformity ccompanies each sling.

