



## Green Pin<sup>®</sup> Bow Shackle BN

Standard bow shackle with safety bolt



### Highlights

- ✓ Double safety (cotter pin & safety bolt)
- ✓ Galvanization assures long-term durability
- ✓ Suitable for both one-leg and multi-leg systems
- ✓ Conforms to wide range of certifications (e.g. DNV)
- ✓ Superior stock availability of 99%

### Description

The Green Pin<sup>®</sup> Bow Shackle BN is a bow shackle with a safety bolt. The shackle offers a double safety (split pin and safety bolt) which prevents accidental unscrewing of the pin. Long-term durability is assured due to the galvanization of the Green Pin<sup>®</sup> Bow Shackle BN. Of course, the Green Pin<sup>®</sup> Bow Shackle BN conforms to a wide range of certifications from class societies such as DNV GL. The Green Pin<sup>®</sup> Bow Shackle BN is suitable for both one-leg and multi-leg systems and is available in a range with a working load limit from 0.5 up to 85 ton.

### Product details

<b>Productcode</b>	G-4163
<b>Material</b>	bow and pin high tensile steel, Grade 6, quenched and tempered
<b>Safety factor</b>	MBL equals 6 x WLL
<b>Finish</b>	hot dipped galvanized
<b>Certification</b>	<b>2.1 2.2 3.1 MTCa DNV 2.7-1a DNV 2.7-1b</b> <b>DNVGL-ST-0378 CE ABS PDA ABS MA</b>
<b>Standard</b>	EN 13889 and meets performance requirements of US Fed. Spec. RR-C-271, Type IVA, Class 3, Grade A. From 2 t and upward these shackles comply with ASME B30.26



## Green Pin® Bow Shackle BN

### Technical specifications in millimeters

Article code	working load limit	Net weight	A diameter bow	B diameter pin	C diameter eye	D width eye	E width inside	F length inside	G width bow	H length	I length bolt	J width	K thickness nut	Nett weight KG
GPGHMB06	0,5	0.06	7	8	16	7	12	29	20	48	42	34	4	0.06
GPGHMB08	0,75	0.11	9	10	20	9	13,5	32	22	56	50	40	5	0.11
GPGHMB10	1	0.16	10	11	23	10	17	37	26	64	60	46	8	0.16
GPGHMB11	1,5	0.22	11	13	25	11	19	43	29	73	67	51	11	0.22
GPGHMB13	2	0.42	13,5	16	34	13	22	51	32	90	80	59	13	0.42
GPGHMB16	3,25	0.74	16	19	40	16	27	64	43	110	98	75	17	0.74
GPGHMB19	4,75	1.18	19	22	46	19	31	76	51	129	115	89	19	1.18
GPGHMB22	6,5	1.77	22	25	52	22	36	83	58	144	130	102	22	1.77
GPGHMB25	8,5	2.58	25	28	59	25	43	95	68	164	150	118	25	2.58
GPGHMB28	9,5	3.66	28	32	67	28	47	108	75	186	166	131	27	3.66
GPGHMB32	12	4.91	32	35	73	32	51	115	83	201	184	147	30	4.91
GPGHMB35	13,5	6.54	35	38	79	35	57	133	92	227	197	162	33	6.54



## Green Pin® Bow Shackle BN

### Technical specifications in millimeters

Article code	working load limit	Net weight	A diameter bow	B diameter pin	C diameter eye	D width eye	E width inside	F length inside	G width bow	H length	I length bolt	J width	K thickness nut	Nett weight KG
GPGHMB38	17	8.19	38	42	88	38	60	146	99	249	202	175	19	8.19
GPGHMB45	25	14.0	45	50	104	45	74	178	126	300	243	216	23	14.0
GPGHMB50	35	18.8	50	57	112	50	83	197	138	332	269	238	26	18.8
GPGHMB57	42,5	28.3	57	65	132	57	95	222	160	378	301	274	29	28.3
GPGHMB65	55	39.6	65	70	145	65	105	260	180	433	329	310	32	39.6
GPGHMB75	85	62.0	75	83	167	75	127	330	190	530	381	340	39	62

[www.greenpin.com](http://www.greenpin.com)



## Green Pin® Bow Shackle BN

### Technical specifications in inches

Article code	working load limit	Net weight	A diameter bow (inch)	B diameter pin (inch)	C diameter eye (inch)	D width eye (inch)	E width inside (inch)	F length inside (inch)	G width bow (inch)	H length (inch)	I length bolt (inch)	J width (inch)	K thickness nut (inch)	Nett weight LBS
GPGHMB06	0,5	0.13	1/4	5/16	5/8	9/32	15/32	1 5/32	25/32	1 7/8	1 21/32	1 11/32	5/32	0.13
GPGHMB08	0,75	0.25	5/16	3/8	25/32	11/32	17/32	1 1/4	7/8	2 7/32	1 31/32	1 9/16	3/16	0.25
GPGHMB10	1	0.34	3/8	7/16	29/32	13/32	21/32	1 15/32	1 1/32	2 17/32	2 3/8	1 13/16	5/16	0.34
GPGHMB11	1,5	0.48	7/16	1/2	31/32	7/16	3/4	1 11/16	1 5/32	2 7/8	2 5/8	2	7/16	0.48
GPGHMB13	2	0.92	1/2	5/8	1 11/32	1/2	7/8	2	1 1/4	3 17/32	3 5/32	2 5/16	1/2	0.92
GPGHMB16	3,25	1.62	5/8	3/4	1 9/16	5/8	1 1/16	2 17/32	1 11/16	4 11/32	3 27/32	2 15/16	21/32	1.62
GPGHMB19	4,75	2.59	3/4	7/8	1 13/16	3/4	1 7/32	3	2	5 3/32	4 17/32	3 1/2	3/4	2.59
GPGHMB22	6,5	3.90	7/8	1	2 1/16	7/8	1 13/32	3 9/32	2 9/32	5 21/32	5 1/8	4 1/32	7/8	3.90
GPGHMB25	8,5	5.69	1	1 1/8	2 5/16	31/32	1 11/16	3 3/4	2 11/16	6 15/32	5 29/32	4 21/32	31/32	5.69
GPGHMB28	9,5	8.07	1 1/8	1 1/4	2 5/8	1 3/32	1 27/32	4 1/4	2 15/16	7 5/16	6 17/32	5 5/32	1 1/16	8.07
GPGHMB32	12	10.8	1 1/4	1 3/8	2 7/8	1 1/4	2	4 17/32	3 9/32	7 29/32	7 1/4	5 25/32	1 3/16	10.8
GPGHMB35	13,5	14.4	1 3/8	1 1/2	3 1/8	1 3/8	2 1/4	5 1/4	3 5/8	8 15/16	7 3/4	6 3/8	1 5/16	14.4



## Green Pin® Bow Shackle BN

### Technical specifications in inches

Article code	working load limit	Net weight	A diameter bow (inch)	B diameter pin (inch)	C diameter eye (inch)	D width eye (inch)	E width inside (inch)	F length inside (inch)	G width bow (inch)	H length (inch)	I length bolt (inch)	J width (inch)	K thickness nut (inch)	Nett weight LBS
GPGHMB38	17	18.1	1 1/2	1 5/8	3 15/32	1 1/2	2 3/8	5 3/4	3 29/32	9 13/16	7 15/16	6 7/8	3/4	18.1
GPGHMB45	25	30.8	1 3/4	2	4 3/32	1 25/32	2 29/32	7	4 31/32	11 13/16	9 9/16	8 1/2	29/32	30.8
GPGHMB50	35	41.5	2	2 1/4	4 13/32	1 31/32	3 9/32	7 3/4	5 7/16	13 1/16	10 19/32	9 3/8	1 1/32	41.5
GPGHMB57	42,5	62.5	2 1/4	2 9/16	5 3/16	2 1/4	3 3/4	8 3/4	6 5/16	14 7/8	11 27/32	10 23/32	1 5/32	62.5
GPGHMB65	55	87.3	2 1/2	2 3/4	5 23/32	2 9/16	4 1/8	10 1/4	7 3/32	17 1/16	12 15/16	12 7/32	1 1/4	87.3
GPGHMB75	85	137	3	3 1/4	6 9/16	2 15/16	5	13	7 15/32	20 7/8	15	13 3/8	1 17/32	137

[www.greenpin.com](http://www.greenpin.com)



## Green Pin® Bow Shackle BN

### Technical drawing

