


REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	PROOF TEST WAS 125%. ADDED NOTE 8	12-18-13	DAH
B	PROOF TEST WAS 150%	06-01-18	DAH

This document contains the proprietary information of Tandemloc, Inc. and your access and use shall be, and is at all times, pursuant to and limited by the Tandemloc, Inc. Terms of Use.

You shall not, and shall not encourage, assist, or authorize another party to copy, distribute, publicly display, modify, reverse engineer, decompile, or take any other action to reproduce this document or the information contained herein.

©2019 by Tandemloc, Inc.
 Dimensions are subject to manufacturing tolerance and change.



NOTES:

- PART NO.: AL50D00-00A-PA, 20 TON WLL LIFT BEAM WITH SHACKLES
 AL50D00-NSA-PA, 20 TON WLL LIFT BEAM NO SHACKLES
- WLL: 20T (40,000 LB.)
- PROOF TESTED TO 125% (50,000 LB.) AND CERTIFIED
- STANDARD SPECIFICATION # EAD21000A APPLIES
- FINISH: SANDBLAST, PRIME AND PAINT SAFETY YELLOW
- CALCULATED WEIGHT: 2,524 LB. W/ SHACKLES 2,432 LB. W/OUT SHACKLES
- DESIGNED AND MANUFACTURED TO MEET OR EXCEED ASME B30.20 AND BTH-1, DESIGN CATEGORY B, SERVICE CLASS 0.
- NDT-PRE & POST LOAD TEST.

**** DO NOT SIGN IF CHANGES ARE REQUIRED ****
 CUSTOMER APPROVAL: _____
 DATE: _____

<input checked="" type="checkbox"/> "X" DENOTES APPLICABLE DATA UNLESS OTHERWISE NOTED. DIMENSIONS ARE IN INCHES & TOLERANCES ARE: .XX ±.00 .XXXX ±.0007 .XXX ±.03	<input type="checkbox"/> "Y" DENOTES APPLICABLE DATA LOST MAX CASTING TOL. IS: 0 TO 4" ±.030", 4.01" TO 7" ±.038" 7.01" TO 10.5" ±.045" OVER 10.5" ±.052"	TANDEMLOC TITLE AL50D00-00A-PA 20 TON WLL LIFT BEAM	
		THIS DOCUMENT CONTAINS DATA WHICH IS EITHER PATENTED, PATENT PENDING OR IS THE PROPERTY OF TANDEMLOC, INC. DISCLOSURE, OR COPYING WITHOUT THE WRITTEN AUTHORIZATION OF TANDEMLOC, INC. IS EXPRESSLY PROHIBITED.	APPROVALS DRN DAH DATE 12-17-13